



US009115958B2

(12) **United States Patent**
Crispin

(10) **Patent No.:** **US 9,115,958 B2**

(45) **Date of Patent:** **Aug. 25, 2015**

(54) **DUAL FIELD OPTICAL AIMING SYSTEM
FOR PROJECTILE WEAPONS**

(71) Applicant: **Leupold & Stevens, Inc.**, Beaverton,
OR (US)

(72) Inventor: **Quint Crispin**, Beaverton, OR (US)

(73) Assignee: **Leupold & Stevens, Inc.**, Beaverton,
OR (US)

2,512,153	A	6/1950	Heney et al.	
2,527,719	A	10/1950	Greenstein et al.	
3,339,450	A *	9/1967	Reed	356/254
3,992,782	A *	11/1976	Rickert	42/120
5,084,780	A	1/1992	Phillips	
5,161,051	A	11/1992	Whitney et al.	
5,349,469	A	9/1994	Francis	
5,383,278	A *	1/1995	Kay	33/265
5,652,679	A *	7/1997	Freeman	359/731
5,877,902	A	3/1999	Sauter	

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 18 days.

(21) Appl. No.: **13/843,445**

(22) Filed: **Mar. 15, 2013**

(65) **Prior Publication Data**

US 2014/0259853 A1 Sep. 18, 2014

(51) **Int. Cl.**
F41G 1/38 (2006.01)
G02B 23/14 (2006.01)
F41G 1/30 (2006.01)

(52) **U.S. Cl.**
CPC .. **F41G 1/38** (2013.01); **F41G 1/30** (2013.01);
G02B 23/14 (2013.01)

(58) **Field of Classification Search**
CPC F41G 1/30; F41G 1/38; F41G 1/34;
F41G 1/17; G02B 23/10; G02B 23/105
USPC 42/111–148
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,225,037	A	12/1940	Dake	
2,388,673	A *	11/1945	Brown	359/420

FOREIGN PATENT DOCUMENTS

EP	0234180	A1	9/1987
EP	2 557 450	A1	2/2013
WO	WO 2012/058453	A2	5/2012

OTHER PUBLICATIONS

Wikipedia, Holographic Weapon Sight, en.wikipedia.org/wiki/Holo-
graphic_weapon_sight, published Jan. 28, 2013, 2 pages.

(Continued)


Primary Examiner — Samir Abdosh

(74) *Attorney, Agent, or Firm* — Stoel Rives LLP

(57) **ABSTRACT**

A system for aiming a projectile weapon includes a telescopic sight for use with a second sighting device, such as a reflex sight or other non-magnifying sight. The telescopic sight has an eye point spaced apart rearwardly from its eyepiece and positioned at a vertical plane containing a line of initial trajectory of the weapon to which the aiming system is mounted so that a line parallel to the line of initial trajectory does not intersect the eyepiece. The location of the eye point facilitates concurrent use of a second sighting device at a normal mounting height and viewable past the eyepiece, thereby allowing the viewer to change views between the telescopic sight and the second sighting device with little eye movement and essentially no head movement.

27 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS


6,005,711 A 12/1999 Mai et al.
 6,487,809 B1 12/2002 Gaber
 6,598,333 B1 * 7/2003 Randazzo et al. 42/127
 6,608,298 B2 8/2003 Gaber
 7,827,723 B1 11/2010 Zaderey et al.
 2011/0035980 A1 * 2/2011 Raviv et al. 42/1.02
 2011/0041377 A1 2/2011 Thomas et al.
 2011/0067288 A1 3/2011 Hakansson et al.


2011/0232152 A1 * 9/2011 Thomas et al. 42/125
 2013/0008072 A1 * 1/2013 Chung 42/113



OTHER PUBLICATIONS


L-3 Communications, EOTech Holographic Weapons Systems, HHS II, www.eotech-inc.com/products/sights/hhs2, visited Mar. 7, 2013, 2 pages.
 European Search Report dated May 19, 2014 for European Application No. 14160137.7.


* cited by examiner






















FIG. 8










FIG. 14

1

DUAL FIELD OPTICAL AIMING SYSTEM FOR PROJECTILE WEAPONS

TECHNICAL FIELD

The field of the present disclosure relates to sighting systems for projectile weapons and, more particularly, to a telescopic sight designed for use with a reflex sight or other non-magnifying sight.

BACKGROUND

Conventional riflescopes and other telescopic sights accomplish magnification changes by optical elements that are either movable along the optical path, or that are switched into and out of the optical path. Also known are sight designs utilizing switching mirrors and/or beam splitters for switching between one of two different optical systems alternately viewable through a common eyepiece. Some sights include optical paths for day and night operation, including visible and infrared channels, which may be combined and superimposed for viewing as a composite image. In many of these systems, components of the sight must be manually moved to switch between viewing modes, which makes the sight more complicated, prone to image instability or misalignment, cumbersome and slow for switching between modes, and prone to making noise.

U.S. Pat. No. 2,388,673 of Brown, U.S. Pat. No. 2,512,153 of Henvey et al., and U.S. Pat. No. 2,527,719 of Greenstein et al. describe dual optical power split-field telescopic sights utilizing different lenses or lens segments for upper and lower portions of the optical system. These telescopic sights utilize complex lens systems and optical prescriptions, and are limited by a shared eyepiece through which both fields are simultaneously viewed.

The present inventors have recognized a need for an aiming system that facilitates viewing a target scene through a telescopic sight and through a second sight having a different field of view or aiming capability, such as a non-magnifying reflex sight providing a wide field of view, very little field obstruction, and fast target acquisition. Various known systems utilize a miniature reflex sight (also known as a red-dot sight) mounted atop a telescopic sight, but the height of the viewing region of the reflex sight in such systems is generally much higher than the exit pupil of the telescopic sight and too high for achieving a cheek weld with the rifle stock (buttstock) as is desirable for stable aiming. Substantial head movement is also needed to switch between the two sights. The required head movement can be cumbersome and slow, particularly when switching from the reflex sight to the telescopic sight and re-aligning the eye with the typically small exit pupil of the telescopic sight.

SUMMARY

In accordance with the present disclosure, a telescopic sight of a projectile weapon aiming system includes a housing supporting an optical system of the telescopic sight relative to a mounting surface of the sight, which may include an integrated mounting bracket or clamp at least partly formed in the housing. An objective of the optical system is horizontally offset relative to a vertical plane containing a line of initial trajectory of the projectile weapon when the telescopic sight is mounted to the projectile weapon. A light redirection device, such as a prism system or set of mirrors, receives light from the objective and causes an image of the field of view formed at a focal plane to be horizontally offset from the

2

objective. In some embodiments, the light redirection device includes a first reflective surface that receives light from the objective and reflects it forwardly along a first path segment toward a second reflective surface that reflects the light rearward along a second path segment that is angled upwardly away from the line of initial trajectory when the telescopic sight is mounted to the weapon.

An eyepiece of the telescopic sight is positioned rearward of the focal plane and defines an eye point spaced apart rearwardly from the eyepiece at which the image of the field of view is visible through the eyepiece. The eye point is located in the vertical plane with the line of initial trajectory and on a line parallel to the line of initial trajectory that does not intersect the eyepiece. The eye point facilitates concurrent use of a second sighting device, such as a non-magnifying reflex sight or holographic weapon sight, that may be viewable past the eyepiece, thereby allowing the viewer to change views between the telescopic sight and the non-magnifying sight with little eye movement and essentially no head movement. It may also enable a shooter to change views between the two sights without breaking cheek weld with a stock of the weapon.

The non-magnifying sight and telescopic sight may be independently mountable in tandem on a common mounting rail of the projectile weapon. Alternatively, the telescopic sight may include a mounting platform that facilitates mounting a reflex sight on the telescopic sight at essentially the same level as the eye point so that a centroid of a viewing window (partial reflector) of the reflex sight is approximately 1.3 to 1.75 inches above a top surface of the mounting rail. Other mounting arrangements may also be possible.

Reticles and alignment subsystems of the telescopic sight for aim point indication and point of aim adjustment (sighting-in) are also disclosed.

Additional aspects and advantages will be apparent from the following detailed description of preferred embodiments, which proceeds with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a rear right side isometric view of an optical aiming system including a telescopic sight shown mounted to a rifle and a reflex sight mounted atop the telescopic sight, according to a first embodiment;

FIG. 2 is a front left side isometric view of the aiming system and rifle of FIG. 1;

FIG. 3 is an isometric view of the telescopic sight component of the aiming system of FIGS. 1-2, with the rifle and reflex sight omitted to show detail;

FIG. 4 is an isometric view of an optical system of the telescopic sight of FIG. 3, annotated to trace an optical path of the telescopic sight;

FIG. 5 is a left side elevation view of the optical system of the aiming system of FIGS. 1 and 2 and illustrating the optical path of the telescopic sight and lines of sight from an eye point;

FIG. 6 is an isometric view of an optical aiming system including the telescopic sight of FIG. 4 and a holographic sight mounted to a common mounting rail of a rifle, according to another embodiment;

FIG. 7 is a rear perspective view of the optical aiming system of FIG. 6 with the rifle omitted;

FIGS. 8, 9 and 10 are respective top plan, right side elevation, and eyepiece end views of an optical aiming system according to yet another embodiment;

3

FIG. 11 is a top plan view of an optical system of the aiming system of FIGS. 8-10, with a reflex sight viewing window omitted;

FIG. 12 is a right side elevation view of the optical system of FIG. 11, together with a viewing window of a reflex sight of the aiming system of FIGS. 8-10;

FIG. 13 is a view of a reticle of the telescopic sight of FIGS. 1-7; and

FIG. 14 is a top view of a telescopic sight with a pivoting mirror for switching the optical path to an auxiliary display.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIGS. 1 and 2 illustrate an optical aiming system 10 according to a first embodiment, shown mounted to a rifle 14. Aiming system 10 includes a telescopic sight 20 mounted to a mounting rail 26 of rifle 14, which may comprise a Picatinny rail (also known as a MIL-STD-1913 rail), which is a universal dovetail-shaped mounting rail commonly found on AR-15 rifles and other tactical rifles. In the embodiment illustrated in FIGS. 1 and 2, a non-magnifying reflex sight 30 is mounted atop telescopic sight 20. Telescopic sight 20 and non-magnifying sight are mounted in alignment with a bore of a barrel 36 of rifle 14, defining a line of initial trajectory 40 of rifle 14. Line of initial trajectory 40 lies within a vertical plane 50 (FIG. 2) that also longitudinally bisects mounting rail 26. As further described below with reference to FIGS. 3 and 4, an objective 160 of telescopic sight 20 is laterally offset (i.e. horizontally offset) relative to vertical plane 50.

It should be understood that the term “vertical plane” is used herein merely as convenient terminology for a frame of reference, and not to limit plane 50 to being exactly vertical relative to the horizon or gravity (i.e. plumb), even though when a rifle is in use the line of initial trajectory 40 and mounting rail 26 will desirably be arranged in a vertically stacked relationship as illustrated and described. As is known in the art, rifle 14 and aiming system 10 can be canted to the side together, thereby tilting vertical plane 50, albeit potentially impacting bullet drop compensation and parallax compensation functions of a reticle 190, 700 (FIGS. 4 and 13) of aiming system 10 described below. Also, aiming system 10 may be mounted on a side rail (not shown) or other non-standard mount that is not perfectly centered or horizontal relative to a normal shooting position. Moreover while the position of mounting rail 26 relative to vertical plane 50 is a common attribute of a tactical rifle, it should be understood that mounting rail 26 or other mounting features or surfaces of a projectile weapon may not necessarily be centered on vertical plane 50. Thus, unless expressly stated in the claims, the use of the term “vertical plane” is not alone intended to limit the scope of the invention to an arrangement in which a mounting rail or other mounting features have the same shape or position as mounting rail 26 to the projectile weapon or to vertical plane 50, or to an exact placement of the vertical plane relative to mounting rail 26. As discussed below, the position of vertical plane 50 is determined in part by the line of initial trajectory 40 of the projectile weapon and in part by the location of an eye point 280 (FIGS. 4 and 5) of the telescopic sight 20.

FIG. 3 is an isometric view of telescopic sight 20 of aiming system 10, with reflex sight 30 removed, and FIG. 4 is an isometric view of an optical system 100 of telescopic sight. With reference to FIGS. 3 and 4, telescopic sight 20 includes a housing 110 that supports optical system 100 relative to a mounting surface 120 of housing 110. In the embodiment shown, mounting surface 120 comprises surfaces of a mount-

4

ing clamp 124 (FIG. 7) having a longitudinal dovetail shaped slot 128. A fixed portion 132 of clamp 124 includes longitudinal reference surfaces providing primary lateral aiming alignment of telescopic sight 20 relative to mounting rail 26. Preferably, these reference surfaces and the entirety of fixed portion 132 are integrally formed directly in housing 110, by machining from stock material or otherwise. A movable portion of clamp 124 is formed by a clamp shoe 134 illustrated in FIG. 7, which is retained to fixed portion 132 by coupling bolt 136. In other embodiments, mounting surface 120 may take other shapes and forms providing a solid platform or reference that, with mounting rail 26 or other scope mount, precisely aligns telescopic sight 20 and optical system 100 relative to rifle 14 when telescopic sight 20 is mounted thereon. For example, in a conventional riflescope housing, the outer longitudinal surface of a main tube of the scope serves as the mounting surface, which is engaged by mounting rings that are secured to a mounting base on the gun's receiver. The term mounting surface may also encompass multiple surfaces on housing 110 that may or may not lie in a common plane, but achieve alignment of telescopic sight 20 using other mounting devices.

With reference to FIG. 3, an eyepiece 150 of optical system 100 is supported by housing 110 at a rearward opening in eyepiece end 152 thereof. When telescopic sight 20 is mounted on rifle 14, eyepiece 150 is aligned with vertical plane 50 (FIG. 2), such that an optical axis of eyepiece 150 is contained in vertical plane 50. In some other embodiments, such as those illustrated in FIGS. 8-10 discussed below, the optical axis of eyepiece 150 is not contained in vertical plane 50 but intersects vertical plane 50. Housing 110 also includes an auxiliary sight mounting platform 154 including a set of threaded mounting holes 156 formed on a top outer surface of housing 110 forward of eyepiece 150. Auxiliary sight mounting platform 154 is horizontal and is centered on and intersects vertical plane 50 when telescopic sight 20 is mounted on rifle 14. Auxiliary sight mounting platform 154 is preferably recessed horizontally below a top surface 158 of eyepiece end 152 of housing 110 (facing away from line of initial trajectory 40) and below an uppermost edge 159 (FIG. 4) of eyepiece 150 to position a miniature reflex sight or other non-magnifying sight or auxiliary sighting device at a desired or optimal height, as further explained below. Top surface 158 of eyepiece end 152 may be flat, following the contour of an uppermost edge 159 of eyepiece 150 in which a top segment of round eyepiece lenses are removed to provide a clear line of sight for use of reflex sight 30, as further described below with reference to FIG. 5.

Continuing with reference to FIGS. 3 and 4, optical system 100 includes an objective 160 comprising objective lenses 164, which gather and focus light at a first (front) focal plane (FFP, not illustrated). In another embodiment (not shown), objective 160 may comprise a reflector or other suitable objective system. Objective 160 is offset horizontally relative to an eyepiece 150 of optical system 100 in the embodiment illustrated. A folded optical path 170 of optical system 100 extends from objective 160 to eyepiece 150. The folded aspect of optical path 170 is created by a light redirection device 180 that receives light from objective 160 and causes an image of the field of view formed at a rear focal plane (RFP) (located approximately at the plane of an aiming reticle 190 of optical system 100) to be offset horizontally from objective 160. In particular, in the embodiment illustrated, light redirection device 180 includes a first reflective surface consisting of a first mirror 202 that receives light from the objective 160 and reflects it forwardly along a first path fold segment 206 toward a second reflective surface consisting of

5

a second mirror **212**. The first path fold segment **206** may be angled downwardly relative to an optical axis of objective **160** (wherein the optical axis of objective **160** is coincident with a segment of optical path **170** between objective **160** and first mirror **202**), depending on the desired or required geometry of optical system **100**. Second mirror **212** receives light reflected by first mirror **202** and reflects the light rearward along a second path fold segment **216** that is angled upwardly away from the line of initial trajectory **40** to eyepiece **150**, as best shown in FIG. **5**. The light propagating along second path fold segment **216** forms, at the RFP, an image of the field of view of telescopic sight **20**. An erector system **230** including an image-erecting relay lens unit **234** positioned between objective **160** and eyepiece **150** erects an image of the field of view formed at FFP and focuses it at RFP. In the figures, backing caps supporting the mirrors **202**, **212** are omitted, providing a view through openings **242**, **244** (FIGS. **3** and **2**, respectively) in housing **110** through which mirrors **202**, **212** are installed.

In another embodiment (not illustrated), erector system **230** may include a power-varying relay lens system (zoom lens system) interposed between FFP and RFP and including at least one (and typically at least two or more) lens elements selectively movable along the optical path **170** to vary an optical magnification setting of telescopic sight **20**. When a zoom lens system is utilized, the aiming reticle **190** is preferably located at front focal plane FFP to maintain a constant relationship between markings on reticle **190** and the target scene regardless of the magnification setting of the zoom lens system.

Although light redirection device **180** is illustrated as a pair of mirrors **202**, **212**, in other embodiments (not shown) light redirection device may comprise a prism including first and second reflective surfaces. A prism system may be an image-erecting prism system, in which case relay lens system **234** can be omitted, and image-carrying light from objective **160** may be first focused at the plane of reticle **190**. In yet another embodiment, light direction device **180** includes an image sensor and an electronic image display device (not illustrated). In the case of an electronic image sensor and display combination, the image sensor would be located at a focal plane, namely either the focal plane of objective **160** (FFP) or a focal plane of the erector system **230**, and the display would be located either at the focal plane of eyepiece **150** (rear focal plane RFP), or at the front conjugate of erector system **230**. Alternatively, light redirection device **180** might include a type of light guide, such as a light pipe (e.g. a bundle of fine aligned optical fibers forming an image pipe), which may bend the optical path without folding it longitudinally.

One or more of objective lenses **164** are slidably supported on housing **110** for movement transversely of an optical axis of the objective lenses relative to other elements of optical system **100**. In the embodiment illustrated, the lateral position of both objective lenses **164** is adjustable via elevation and windage adjustment screws **250**, **252** (FIG. **3**) that are supported on and extend through housing **110**. In alternative embodiments, another kind of adjustment mechanism may be employed. Adjustment screws **250**, **252** can be manually turned to drive objective lenses **164** in a direction transversely of (and preferably perpendicular to) their optical axis to thereby effect vertical and horizontal aiming adjustments to the line of sight of telescopic sight **20**, for sighting-in the aim point of telescopic sight **20** or compensating for bullet drop and/or wind effects, as further described in U.S. Pat. No. 7,827,723 of Zaderey et al., issued Nov. 9, 2010. Because objective lenses **164** are movable, they are not sealed to the housing **110**. Instead, a transparent sealing window **264** (il-

6

lustrated in FIG. **4**) is fixed to housing **110** forward of objective lenses **164** and hermetically seals an interior of housing **110**. The horizontal offset of objective **160** relative to vertical plane **50** and mounting rail **26** enables elevation adjustment screw **250** to be positioned on an underside of housing **110** while remaining accessible for adjustment via a coin or screwdriver, which further enhances the low profile nature of telescopic sight **20** and avoids elevation adjustment screw **250** from inhibiting the unaided (naked eye) field of view past housing **110**.

A left side elevation view of optical system **100** is illustrated in FIG. **5** together with optical elements of reflex sight **30**. With reference to FIGS. **4** and **5**, eyepiece **150** is positioned rearward of rear focal plane RFP (coplanar with reticle **190**) and defines an eye point **280** spaced rearwardly of eyepiece **150** at which the image of the field of view formed at RFP is visible through eyepiece **150**. First path fold segment **206** is angled downwardly toward second mirror **212** relative to an optical axis **284** of objective **160**. Second mirror **212** receives the light reflected by first mirror **202** and reflects the light rearward along second path fold segment **216**, which is angled upwardly away from initial line of trajectory **40** and toward a horizontal plane containing the optical axis **284** of objective **160**. This down and up folded optical path **170** assists in lowering the position of eyepiece **150** relative to the weapon. In the embodiment illustrated, optical path **170** is folded in both the horizontal and vertical axes, though in other embodiments (not illustrated), optical path **170** may be folded only horizontally or in only a vertical plane **50**.

When telescopic sight **20** is mounted to rifle **14**, eye point **280** is located at a place on vertical plane **50** (FIG. **2**) such that a line **290** (FIG. **5**) parallel to the line of initial trajectory **40** and intersecting eye point **280** does not intersect eyepiece **150**. In the embodiment illustrated in FIGS. **1-7**, eyepiece **150** is truncated and flat along its uppermost edge **159** (i.e., a round lens that has been cut, ground, or otherwise truncated or relieved to remove a section) to allow a clear horizontal line of sight from eye point **280** through a viewing window **300** of reflex sight **30** mounted forwardly of eyepiece **150**. The truncated uppermost edge **159** of eyepiece may also enable a relatively large range of eye positions for use of reflex sight (beyond eye point **280**), which may facilitate fast target acquisition in close-quarter tactical situations. Eye point **280** is preferably located just above a horizontal plane **294** tangent to uppermost edge **159** of eyepiece **150**, which faces away from line of initial trajectory **40** when telescopic sight **20** is mounted to rifle **14** or another projectile weapon. Skilled persons will appreciate that eye point **280** may be any point within an exit pupil of telescopic sight **20** at which a viewer's eye **330** may be located to view the entire image of the field of view of telescopic sight **20**.

Reflex sight **30** includes a light source **310**, such as an LED, which is positioned near a focal point of viewing window **300**, which is curved and includes a partial reflector in the form of a dichroic reflective surface **314**. The dichroic reflective surface **314** of viewing window **300** selectively reflects the wavelength of illumination emitted by light source **310** while passing other wavelengths of light, so as to reflect collimated light **320** toward the viewer's eye **330** while allowing the viewer to see a distant target scene through viewing window **300**. As is well known in the art, this arrangement results in an image of an aiming mark or reticle formed by light source **310** to appear focused at a distance forward of reflex sight **30** and superimposed on the target scene viewed through viewing window **300** to enable accurate aiming across a relatively wide range of head and eye positions at which the collimated light is received by the viewer's eye **330**.

7

Viewing window **300** is positioned predominantly above the horizontal plane **294** when both reflex sight **30** and telescopic sight **20** are mounted to rifle **14**, such that both telescopic sight **20** and reflex sight **30** can be used to aim rifle **14** with essentially no movement of the viewer's head. In practice, a small portion of the base of viewing window **300** may lie below horizontal plane **294**, which will only slightly reduce the effective range of eye positions at which reflex sight **30** can be used for aiming. The shooter or viewer may easily change between a (magnified) viewing line of sight **334** of telescopic sight **20** and a non-magnified viewing line of sight **336** through reflex sight **30** merely by rotating the viewer's eye **330** within its socket and with essentially no head movement. Thus, in practice when switching between sights **20** and **30**, the eye point **280** of telescopic sight **20** (along viewing line of sight **334**) may be slightly below and spaced apart from an eye point of viewer's eye **330** when viewing through reflex sight along viewing line of sight **336**. Alternatively, both sights **20**, **30** may be viewed from coincident eye points. When the telescopic sight **20** and reflex sight **30** are mounted to mounting rail **26** of rifle **14**, a centroid of the surface area of viewing window **300** is preferably located between 1.3 and 1.75 inches above mounting rail **26**, and more preferably between 1.3 and 1.6 inches or between 1.4 and 1.5 inches above mounting rail **26**, which is an ideal height for allowing a shooter to form a cheek weld with a stock **340** (FIG. 1) of rifle **14**. Thus, telescopic sight **20** and reflex sight **30** may be sequentially used for aiming without breaking the cheek weld.

FIG. 6 illustrates an aiming system **400** according to another embodiment, in which a non-magnifying holographic weapon sight **420** and telescopic sight **20** are independently mounted to mounting rail **26** of rifle **14** in tandem. Holographic weapon sight may be any of a variety of holographic sights sold by EOTech, a subsidiary of L-3 Communications located in Ann Arbor, Mich. In the tandem mounting arrangement, each of telescopic sight **20** and holographic weapon sight **420** is separately removable and mountable to the common mounting rail **26** independently of the other. In this arrangement, the sights are independently sighted in. The sights can be targeted at different sighted-in ranges. Or if a common sighted-in range is desired, the second one of the sights to be mounted can be sighted in merely by positioning its aiming mark at the same place on the target scene as the other sight, which has been previously sighted-in.

FIG. 7 is a rear perspective view of aiming system **400** illustrating how a viewing window (optic **430**) is in a vertically stacked relationship with eyepiece **150**. In practice, the fields of view of telescopic sight **20** and the non-magnifying sight (either holographic weapon sight **420**, or in the embodiment of FIGS. 1-7, reflex sight **30**) may be stacked directly adjacent each other to form a composite image in which the top portion of the composite image is a wide-field of view of the scene with no magnification and the bottom portion of the composite image is a narrow field of view of a magnified image of the same scene of the distant target. In some embodiments, the two images may be slightly spaced apart or divided by an edge of eyepiece end **152** of housing **110** to provide a distinct separation between images and avoid confusion.

Other types of non-magnifying sights may also be utilized with telescopic sights according to the present disclosure. For example, reflex sights having a collimated light source and a flat partially reflective viewing window may be utilized. Still other non-magnifying sights, such as iron sights, may be usable with telescopic sights and aiming systems (including a secondary reflex sight or other non-magnifying sight). Mounting a non-magnifying sight, such as reflex sight **30** or

8

holographic weapon sight **420**, at a normal mounting height in the range of 1.3 to 1.75 inches enables the user to co-witness the non-magnifying sight with conventional iron sights (not illustrated), which may include a front iron sight located forward of aiming system **10** toward a muzzle end of barrel **36**, and a rear iron sight located behind the front iron sight and behind or forward of aiming system **10**.

Skilled persons will appreciate that the aiming systems **10** and **400** of FIGS. 1-7 are right-handed and designed to be viewed using the shooter's right eye, and their configuration provides a right-handed shooter with little impediment to viewing the target scene with a naked left eye. However, if the same aiming systems **10** and **400** were to be used by a left-handed shooter, the objective **160** and the portion of housing **110** associated therewith would tend to block the unaided field of view of the shooter's right eye. A left-handed embodiment of the aiming systems (not shown) is also contemplated, in which the objective **160** is horizontally offset to the left of the vertical plane **50**.

FIGS. 8, 9 and 10 show respective top, right side, and eyepiece end views of an aiming system **500** according to yet another embodiment, including a telescopic sight **506** having an objective **510** offset laterally to the left of a vertical plane (illustrated by centerline **530** in FIG. 8) and an eyepiece **520** offset laterally to the right of vertical plane **530**. Portions of a housing **540** of telescopic sight **506** are cut away to reveal portions of an optical system **508** of telescopic sight **506**. FIG. 11 is a top view of optical system **508** of telescopic sight, and FIG. 12 is a side elevation view of optical system **508**. FIG. 12 also illustrates a viewing window **556** of a reflex sight **550** of aiming system **500**.

With reference to FIGS. 8-12, reflex sight **550** is mounted along a central portion of the housing **540** of telescopic sight **506** between objective **510** and eyepiece **520**. A first mirror **560** receives light from objective **510** and reflects it forwardly and across vertical plane **530** and at a slight downward angle relative to the optical axis **564** of objective **510** through an image-erecting reflex lens unit **570** to a second mirror **580**. Second mirror **580** reflects the light rearward and toward vertical plane **530** to a rear focal plane (RFP) located at or near a reticle **590** (FIGS. 11 and 12). Eyepiece **520** defines an eye point **600** rearward of eyepiece **520** at which the image at the RFP is visible. The eye point **600** is located at a place on vertical plane **530** such that a line parallel to the initial line of trajectory (not illustrated) extends through viewing window **556** of reflex sight and does not intersect eyepiece **520**. Due to the lateral offset of eyepiece **520**, eye point **600** may, in some embodiments, be lower than a horizontal plane (not illustrated) tangent to an uppermost edge **610** (FIG. 12) of eyepiece **520**, yet a horizontal line of sight intersecting eye point **600** and contained in vertical plane **530** does not intersect eyepiece **520**. A similar lateral arrangement of eyepiece **520** may also enable reflex sight **550** to be mounted relatively low on telescopic sight **506** such that a lower edge **620** (FIG. 12) of viewing window **556** is vertically lower than the uppermost edge **610** of eyepiece **520** without occluding an effective field of view through viewing window **556**, as best illustrated in FIG. 10.

In still other embodiments (not illustrated) a telescopic sight with a folded optical path may include a small diameter objective centered on the weapon (on vertical plane **530**); and with an eyepiece that is laterally offset to the side of vertical plane **530**, similarly to telescopic sight **506** of FIGS. 8-12. A small diameter objective may allow reflex sight to be mounted atop the telescopic sight while maintaining a height of a centroid of the viewing window of reflex sight at a height of between 1.3 and 1.75 inch above the mounting rail (not

shown). Like the embodiment of FIGS. 8-12, the eyepiece is angled inwardly and upwardly to provide an eye point that allows both the telescopic sight and the reflex sight mounted thereon to be viewed from essentially the same head position and with little eye movement, and to provide other benefits described above with respect to FIGS. 8-12 while avoiding the parallax issues addressed by the reticle described below.

FIG. 13 is a view of a reticle 700 usable in place of reticle 190 of telescopic sight 20 (FIGS. 4 and 5). With reference to FIG. 13, reticle 700 includes a primary aiming mark 710 at the center of a horseshoe shape 712. A vertical aiming axis (shown partially by dimension line 716, which forms no part of reticle 700) extends through aiming mark 710. Reticle 700 is designed so that, when telescopic sight 20 is sighted-in with primary aiming mark 710 accurately aiming at a point of impact of the projectile at the sighted-in distance (for example 100 or 200 yards), holdover aiming marks 720, 730, 740, 750 provide compensation for different ranges (e.g. 300, 400, 500, and 600 yards, etc.). Holdover aiming marks 720, 730, 740, and 750 are spaced below primary aiming mark 710 and laterally offset to the right side of vertical aiming axis to compensate for parallax induced by the horizontal offset of the objective 160 to the right of vertical plane 50 and line of initial trajectory 40 and an angled line of sight. More particularly, the position of reticle 700 in telescopic sight 20 (and particularly aiming marks 710, 720, 730, 740, and 750) cooperates with objective 160 to define a line of sight from objective 160 that is angled horizontally inward toward vertical plane 50 when telescopic sight 20 is mounted to rifle 14. Skilled persons will appreciate that this angled line of sight induces left-to-right parallax error at ranges different from the sighted-in range, compensated by laterally offsetting holdover aiming marks 720, 730, 740, 750 relative to vertical axis 716 of reticle 700, as discussed above. The position of holdover aiming marks 720, 730, 740, 750 may also be designed to compensate for spin-drift of the bullet at ranges beyond the sighted-in range.

FIG. 14 is a top view of a telescopic day/night sight 800 similar to telescopic sight of FIGS. 1-7, but in which a second mirror 810 is pivotable to switch the field of view of telescopic sight 800 between a day mode and a night mode. In day mode, the second mirror 810 is in a first position to receive visible light (which has been gathered by objective 820 and reflected by first mirror 830 along a first path fold segment 840) and to reflect the visible light along a second path fold segment 850 to a rear focal plane (RFP) for viewing via the common eyepiece 855. In night mode, the second mirror 810 is pivoted or otherwise moved to a second position, to receive light along a third optical path segment 860 from a display unit 870 of an auxiliary viewing device, such as a thermal imaging device, infrared scope, or other night vision sight, or from another type of video or image input device. In night mode, the image of the display is formed at RFP for viewing via eyepiece 855. A relay lens unit 880 (erector lenses) is provided in third optical path segment 860 between display unit 870 and second mirror 810. In some embodiments, telescopic day/night sight 800 be additionally utilized with a reflex sight or other non-magnifying sight (not illustrated).

It will be obvious to those having skill in the art that many changes may be made to the details of the above-described embodiments without departing from the underlying principles of the invention. For example, while the foregoing description of the aiming system 10 is presented in the environment of a tactical rifle, it should be understood that aiming systems and other aspects of the devices described herein may be used in conjunction with other projectile weapons, such as hunting rifles, handguns (pistols), shotguns, archery bows, crossbows, and grenade launchers, for example, and for other sighting needs unrelated to projectile weapons, such as obser-

vation, surveying, and the like. The scope of the present invention should, therefore, be determined only by the following claims.

The invention claimed is:

1. A projectile weapon aiming system, comprising:

a telescopic sight including a housing having a mounting surface that facilitates mounting the telescopic sight on a projectile weapon in alignment with a line of initial trajectory of the projectile weapon, the housing supporting an optical system of the telescopic sight and positioning the optical system relative to the mounting surface, the optical system including:

an objective horizontally offset relative to a vertical plane containing the line of initial trajectory when the telescopic sight is mounted to the projectile weapon; a light redirection device that receives light from the objective and produces at a focal plane an image of a field of view of the telescopic sight, the image being horizontally offset from the objective; and

an eyepiece positioned rearward of the focal plane and defining an eye point spaced apart rearwardly from the eyepiece at which the image of the field of view is visible through the eyepiece, wherein, when the telescopic sight is mounted to the projectile weapon, the eye point is located at a place on the vertical plane such that a line parallel to the line of initial trajectory and intersecting the eye point does not intersect the telescopic sight.

2. A projectile weapon aiming system, comprising:

a telescopic sight including a housing having a mounting surface that facilitates mounting the telescopic sight on a projectile weapon in alignment with a line of initial trajectory of the projectile weapon, the housing supporting an optical system of the telescopic sight and positioning the optical system relative to the mounting surface, the optical system forming at a focal plane an image of a field of view of the telescopic sight, the optical system including:

an objective having an optical axis horizontally offset relative to a vertical plane containing the line of initial trajectory when the telescopic sight is mounted to the projectile weapon;

a light redirected device that receives light from the objective and redirects the light to a location horizontally offset from the optical axis of the objective; and

an eyepiece positioned rearward of the focal plane and defining an eye point spaced apart rearwardly from the eyepiece at which the image of the field of view is visible through the eyepiece, wherein, when the telescopic sight is mounted to the projectile weapon, the eye point is located at a place on the vertical plane such that a line parallel to the line of initial trajectory and intersecting the eye point does not intersect the eyepiece; and

an aiming reticle located at the focal plane.

3. The aiming system of claim 1, wherein the eye point is located above a horizontal plane tangent to an uppermost edge of the eyepiece that faces away from the line of initial trajectory when the telescopic sight is mounted to the projectile weapon.

4. The aiming system of claim 3, further comprising a non-magnifying sight having a viewing window positioned predominantly above the horizontal plane when both the non-magnifying sight and the telescopic sight are mounted to the projectile weapon, such that both the telescopic sight and the non-magnifying sight can be used to aim the projectile weapon with essentially no movement of the viewer's head.

5. The aiming system of claim 4, wherein the non-magnifying sight and the telescopic sight are independently mount-

11

able in tandem on a common mounting rail of the projectile weapon and separately removable from the common mounting rail.

6. The aiming system of claim 4, wherein the non-magnifying sight is a reflex sight, and the viewing window is a partial reflector. 5

7. The aiming system of claim 4, wherein the non-magnifying sight is a holographic weapon sight.

8. The aiming system of claim 1, wherein:

the optical system defines an optical path extending from the objective to the eyepiece; and 10

the light redirection device includes spaced-apart first and second reflective surfaces arranged to fold the optical path.

9. The aiming system of claim 8, wherein:

the first reflective surface receives light from the objective and reflects it forwardly along a first path fold segment; and 15

the second reflective surface receives the light reflected by the first reflective surface and reflects such light rearward along a second path fold segment that is angled upwardly away from the line of initial trajectory. 20

10. The aiming system of claim 9, wherein the first path fold segment is angled downwardly toward the second reflective surface relative to an optical axis of the objective. 25

11. The aiming system of claim 8, wherein the first and second reflective surfaces comprise respective first and second mirrors.

12. The aiming system of claim 8, wherein the first and second reflective surfaces are surfaces of a prism system. 30

13. The aiming system of claim 1, wherein the light redirection device includes:

an image sensor; and

an electronic image display device positioned at the focal plane and spaced apart from the image sensor. 35

14. The aiming system of claim 1, wherein:

the objective forms a first image of the field of view at a front focal plane;

the focal plane viewed by the eyepiece is a rear focal plane spaced apart from the front focal plane; and 40

the optical system further includes:

an aiming reticle located at the front focal plane; and

a power-varying relay lens system interposed in an optical path between the front focal plane and the rear focal plane and including at least one lens element selectively movable along the optical path to vary an optical magnification of the telescopic sight. 45

15. The aiming system of claim 14, wherein the aiming reticle includes:

a primary aiming mark located on a vertical aiming axis; and 50

multiple holdover aiming marks spaced apart below the primary aiming mark, the holdover aiming marks laterally offset to one side of the vertical aiming axis to compensate for the horizontal offset of the objective. 55

16. The aiming system of claim 2, wherein the aiming reticle includes:

a primary aiming mark located on a vertical aiming axis; and

multiple holdover aiming marks spaced apart below the primary aiming mark, the holdover aiming marks laterally offset to one side of the vertical aiming axis to compensate for the horizontal offset of the objective. 60

17. The aiming system of claim 2, wherein the objective and the aiming reticle define a line of sight angled horizontally inward toward the vertical plane when the telescopic sight is mounted to the projectile weapon. 65

12

18. The aiming system of claim 2, wherein:

the objective and the aiming reticle define a line of sight of the optical system;

the objective includes an objective lens that is slidably supported on the housing for movement transversely of an optical axis of the objective lens relative to other elements of the optical system; and

the telescopic sight further comprises an adjustment mechanism supported on the housing and operable to drive the objective lens transversely of its optical axis to thereby adjust the line of sight of the telescopic sight.

19. The aiming system of claim 1, wherein the mounting surface includes a clamp that is sized and shaped to secure the telescopic sight to a Picatinny rail, the clamp including a fixed portion integrally formed in the housing and a movable jaw portion.

20. The aiming system of claim 1, wherein an outer surface of the housing includes an auxiliary sight mounting platform located forward of the eyepiece, the auxiliary sight mounting platform being horizontal and intersecting the vertical plane when the telescopic sight is mounted to the projectile weapon.

21. The aiming system of claim 20, further comprising a miniature reflex sight mounted to the auxiliary sight mounting platform. 25

22. The aiming system of claim 21, wherein:

the miniature reflex sight has a viewing window; and

when the telescopic sight is mounted to a mounting rail of the projectile weapon, a centroid of the viewing window is located between 1.3 and 1.75 inches above a top surface of the mounting rail.

23. The aiming system of claim 9, wherein the second reflective surface is pivotable from a first position receiving light reflected by the first reflective surface and reflecting such light along the second path fold segment, and a second position in which the second reflective surface receives image-display light from an electronic display device along a third optical path segment angularly offset from the first and second path fold segments and reflects the image-display light along the second path fold segment. 35

24. The aiming system of claim 2, wherein the light redirection device receives light from the objective along a first optical path segment and redirects it rearwardly along a second optical path segment from the light redirection device to the eyepiece, wherein the second optical path segment is spaced apart from the optical axis of the objective and angled upwardly from the line of initial trajectory.

25. The aiming system of claim 2, wherein:

the optical system defines an optical path extending from the objective to the eyepiece; and

the light redirection device includes spaced-apart first and second reflective surfaces arranged to fold the optical path.

26. The aiming system of claim 2, wherein the eye point is located above a horizontal plane tangent to an uppermost edge of the eyepiece that faces away from the line of initial trajectory when the telescopic sight is mounted to the projectile weapon.

27. The aiming system of claim 26, further comprising a non-magnifying sight having a viewing window positioned predominantly above the horizontal plane when both the non-magnifying sight and the telescopic sight are mounted to the projectile weapon, such that both the telescopic sight and the non-magnifying sight can be used to aim the projectile weapon with essentially no movement of the viewer's head. 65

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,115,958 B2
APPLICATION NO. : 13/843445
DATED : August 25, 2015
INVENTOR(S) : Quint Crispin

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

IN THE CLAIMS

In column 10, line 28, please replace “comprising;” with --comprising;--.

In column 10, line 41, please replace “light redirected device” with --light redirection device--.

In column 10, line 46, please replace “at witch” with --at which--.

Signed and Sealed this
Nineteenth Day of January, 2016

A handwritten signature in black ink, reading "Michelle K. Lee". The signature is written in a cursive style with a long, sweeping underline.

Michelle K. Lee
Director of the United States Patent and Trademark Office